IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): Flame-hydrolytically A flame-hydrolytically produced titanium dioxide powder present in aggregates of primary particles, characterised in that

- it has a BET surface of 20 to 200 m²/g and
- the half width HW, in nanometers, of the primary particle distribution has values between

HW [nm] = a H BET^f where a = $670H10^{-9}$ m³/g and -1.3 # f # -1.0 and

the proportion of particles with a diameter of more than 45 μ m is in a range from 0.0001 to 0.05 wt.%.

Claim 2 (Currently Amended): Flame-hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 1, characterised in that wherein the BET surface is in a range from 40 to 60 m²/g.

Claim 3 (Currently Amended): Flame-hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 2, eharacterised in that wherein the 90% spread of the number distribution of the primary particle diameters lies in a range from 5 to 100 nm.

Claim 4 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 2 or 3, characterised in that wherein the equivalent circular diameter of the aggregates (ECD) is less than 80 nm.

Claim 5 (Currently Amended): Flame-hydrolytically The flame-hydrolytically produced titanium dioxide powder according to elaims 2 to 4, characterised in that claim 2, wherein the mean aggregate area is less than 6500 nm².

Claim 6 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to elaims 2 to 5, characterised in that claim 2, wherein the mean aggregate circumference is less than 450 nm.

Claim 7 (Currently Amended): Flame-hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 1, characterised in that wherein the BET surface lies in a range from 80 to 120 m²/g.

Claim 8 (Currently Amended): Flame-hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 7, eharacterised in that wherein the 90% spread of the number distribution of the primary particles diameters has values from 4 to 25 nm.

Claim 9 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claim 7 or 8, characterised in that wherein the equivalent circular diameter of the aggregates (ECD) is less than 70 nm.

Claim 10 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to elaims 7 to 9, characterised in that claim 7, wherein the mean aggregate area is less than 6000 nm².

Claim 11 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claims 7 to 10, characterised in that claim 7, wherein the mean aggregate circumference is less than 400 nm.

Claim 12 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claims 1 to 11, characterised in that claim 1, wherein the proportion of aggregates and/or agglomerates with a diameter of more than 45 µm lies in a range from 0.001 to 0.01 wt.%.

Claim 13 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claims 1 to 12, characterised in that claim 1, wherein for a given BET surface it has an anatase/rutile ratio of 2:98 to 98:2.

Claim 14 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claims 1 to 13, characterised in that claim 1, wherein it has a chloride content of less than 0.1 wt.%.

Claim 15 (Currently Amended): Flame hydrolytically The flame-hydrolytically produced titanium dioxide powder according to claims 1 to 14, characterised in that claim 1, wherein the compacted bulk density has values of 20 to 200 g/l.

Claim 16 (Currently Amended): Process A process for the production of the flame-hydrolytically produced titanium dioxide powder according to claims 1 to 15, characterised in that claim 1, wherein

- a titanium halide, preferably titanium tetrachloride, is vapourised at temperatures of less than 200°C, the vapours are transferred to a mixing chamber by means of a carrier gas with a proportion of steam in a range from 1 to 25 g/m³, and
- separately from this, hydrogen, primary air, which may optionally be enriched with oxygen and/or pre-heated, and steam are transferred to the mixing chamber,
 - wherein the proportion of steam is in a range from 1 to 25 g/m³ primary air,
 - the lambda value lies in the range from 1 to 9 and the gamma value lies in the range from 1 to 9,

following which

- the mixture consisting of the titanium halide vapour, hydrogen, air and steam is ignited in a burner and the flame burns back into a reaction chamber sealed from the ambient air, wherein
 - a vacuum of 1 to 200 mbar exists in the reaction chamber,
 - the exit velocity of the reaction mixture from the mixing chamber to the reaction space lies in a range from 10 to 80 m/sec,
- in addition secondary air is introduced into the reaction chamber, wherein
 - the ratio of primary air to secondary air is between 10 and 0.5,
- following which the solid is separated from the gaseous substances, and
- the solid is then treated with steam.

290909US0PCT Preliminary Amendment

Claim 17 (Currently Amended): Process The process according to claim 16, characterised in that wherein the steam is introduced together with the air into the mixing chamber.

Claim 18 (Currently Amended): Use of the A flame-hydrolytically produced titanium dioxide powder according to elaims 1 to 15 claim 1 for the heat protection stabilisation of silicones.

Claim 19 (Currently Amended): Use of the Sunscreen agents comprising a flame-hydrolytically produced titanium dioxide powder according to claims 1 to 15 in sunscreen agents claim 1.

Claim 20 (Currently Amended): A catalyst, a catalyst carrier, a photocatalyst, and an abrasive for the production of dispersions comprising a Use of the flame-hydrolytically produced titanium dioxide powder according to claim 1 elaims 1 to 15 as a catalyst, as a catalyst carrier, as a photocatalyst, and as an abrasive for the production of dispersions.